

Product datasheet

Specifications



Easy UPS On-Line SRVS 6000VA 230V

SRVS6KI

Overview

| | |
|---------------------|--|
| Presentation | For small to medium businesses, Easy UPS 1 Ph On-Line provides essential power protection for unstable power conditions, ensuring consistent and reliable connectivity at the most critical moments. |
| Lead time | Usually in Stock |

Main

| | |
|------------------------------|---|
| Main Input Voltage | 230 V |
| Other Input Voltage | 220 V 240 V |
| Main Output Voltage | 230 V |
| Other Output Voltage | 220 V 240 V |
| Rated power in W | 6000 W |
| Rated power in VA | 6000 VA |
| Output connector type | Hard wire 3-wire (H N + E) 1 |
| Provided equipment | Basic UPS signalling RS-232 cable CD with software User manual USB cable |

General

| | |
|--|----|
| Number of power module filled slots | 0 |
| Number of power module free slots | 0 |
| Redundant | No |

Physical

| | |
|----------------------------|---------------|
| Colour | Black |
| Height | 68.5 cm |
| Width | 19 cm |
| Depth | 37.4 cm |
| Net weight | 54 kg |
| Mounting location | Front |
| Mounting preference | No preference |

| | |
|--------------------------|--------------------|
| Mounting mode | Not rack-mountable |
| USB compatible | Yes |
| Mounting position | Vertical |

Input

| | |
|-----------------------------------|--|
| Input voltage limits | 110...300 V half load 176...300 V full load |
| Number of input connectors | 1 hard wire 3-wire |
| Network frequency | 40...70 Hz auto sensing |

Output

| | |
|---|--|
| Maximum configurable power in VA | 6000 VA |
| Maximum configurable power in W | 6000 W |
| Output frequency | 50/60 Hz +/- 3 Hz sync to mains |
| UPS type | Double conversion online |
| Wave type | Sine wave |
| Efficiency | 94 % (full load) |
| Additional information | Configurable for 220 : 230 or 240 nominal output voltage |
| Bypass type | Internal bypass (automatic and manual) |
| Crest factor | 3 : 1 |

Conformance

| | |
|-------------------------------|----------------------------------|
| Product certifications | CE |
| Standards | EN/IEC 62040-1 EN/IEC 62040-2 |

Environmental

| | |
|--|-------------------------|
| Ambient air temperature for operation | 0...40 °C |
| Relative humidity | 0...95 % non-condensing |
| Operating altitude | 0...3000 m |
| Ambient air temperature for storage | -15...60 °C |
| Storage Relative Humidity | 0...95 % Non-condensing |
| Storage altitude | 0...15000 m |
| Acoustic level | 55 dBA |
| IP degree of protection | IP20 |

Batteries & Runtime

| | |
|---------------------------------------|-------------------|
| Battery type | Lead-acid battery |
| Battery voltage | 192 V |
| Number of battery filled slots | 0 |
| Number of battery free slots | 0 |
| Battery life | 3...5 year(s) |
| Battery charger power | 112400 W rated |

Communications & Management

| | |
|---------------------|--|
| Alarm | Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm |
| Control panel | Multifunction LCD status and control console |
| Emergency power off | Yes |
| Free slots | 1 |

Surge Protection and Filtering

| | |
|-------------------|-------|
| Surge energy rate | 600 J |
|-------------------|-------|

Packing Units

| | |
|------------------------------|---------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Weight | 66 kg |
| Package 1 Height | 91 cm |
| Package 1 width | 29 cm |
| Package 1 Length | 49.5 cm |

Offer Sustainability

| | |
|----------------------------|---|
| REACH Regulation | REACH Declaration |
| EU RoHS Directive | Compliant EU RoHS Declaration |
| Mercury free | Yes |
| RoHS exemption information | Yes |
| China RoHS Regulation | China RoHS declaration Product out of China RoHS scope. Substance declaration for your information |
| WEEE | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |

Contractual warranty

| | |
|----------|---------------------------|
| Warranty | 2 years repair or replace |
|----------|---------------------------|