

Product datasheet

Specifications



Easy UPS 3S 10 kVA 400 V 3:3 UPS for internal batteries

E3SUPS10KHB

Overview

Presentation

High-efficiency 3-phase UPS that features advanced product features, competitive specifications, and robust electrical design, making business continuity easy in the data center or electrical room. This is an exceptionally easy to install, operate, maintain, and service 10 kVA UPS, ideal for small and medium businesses. Includes dust filter and conformance-coated boards for harsh environments. This UPS is for internal batteries, but is supplied without batteries, so you can easily customize the battery runtime. For battery runtime details, see the runtime charts published under the Documents tab.

Lead time

Usually Ships within 6 Weeks

Main

Main Input Voltage 400 V 3 phases

Other Input Voltage 380 V
415 V

Main Output Voltage 400 V 3 phases

Other Output Voltage 380 V
415 V

Rated power in W 10 kW

Rated power in VA 10 kVA

Provided equipment Dust filter
Installation guide

Physical

Colour White (RAL 9003)

Height 140 cm

Width 38 cm

Depth 92.8 cm

Net weight 112 kg

USB compatible Yes

Input

Maximum input current 18 A

Input harmonic distortion Less than 3 % for full load

Load power factor 0.9 leading to 0.9 lagging

Input Power Factor at Full Load 0.99

Input voltage limits 304...477 V

Network frequency	45...65 Hz
-------------------	------------

Output

Maximum configurable power in VA	10 kVA
----------------------------------	--------

Maximum configurable power in W	10 kW
---------------------------------	-------

Output frequency	50 Hz sync to mains 60 Hz sync to mains
------------------	--

Harmonic distortion	Less than 3 %
---------------------	---------------

Output harmonic distortion	< 3% linear load
----------------------------	------------------

Output overload operation	130-150% for 1 minute and 125-130% for 10 minutes
---------------------------	---

Output voltage tolerance	+/- 1.5 %
--------------------------	-----------

UPS type	Double conversion online
----------	--------------------------

Conformance

Product certifications	CE EAC RCM
------------------------	------------------

Environmental

Ambient air temperature for operation	0...40 °C
---------------------------------------	-----------

Relative humidity	0...95 % non-condensing
-------------------	-------------------------

Operating altitude	0...3333 ft
--------------------	-------------

Ambient air temperature for storage	-15...40 °C
-------------------------------------	-------------

Storage Relative Humidity	Non-condensing 0...95 %
---------------------------	-------------------------

Storage altitude	0.00...15240.00 m
------------------	-------------------

Acoustic level	60 dBA
----------------	--------

Heat dissipation	516 Btu/h
------------------	-----------

IP degree of protection	IP20
-------------------------	------

Batteries & Runtime

Battery type	VRLA
--------------	------

Battery voltage	240 V
-----------------	-------

Maximum short-circuit current	10 kA
-------------------------------	-------

Number of battery filled slots	0
--------------------------------	---

Number of battery free slots	3
------------------------------	---

Discharge battery voltage	+/- 198 V DC
---------------------------	--------------

Packing Units

Unit Type of Package 1	PCE
------------------------	-----

Package 1 Length	56.3 cm
------------------	---------

Number of Units in Package 1	1
------------------------------	---

Package 1 Width	101.4 cm
-----------------	----------

Package 1 Height	164 cm
------------------	--------

Package 1 Weight	145 kg
------------------	--------

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information
Optimized Energy Efficiency	Energy efficient product

Contractual warranty

Warranty	1 year on-site repair or replace with factory authorized Start-Up
-----------------	---